

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 016 385 A2

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
05.07.2000 Bulletin 2000/27

(51) Int. Cl.⁷: A61F 2/34

(21) Application number: 99310569.1

(22) Date of filing: 24.12.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 30.12.1998 US 223486

(71) Applicant:
JOHNSON & JOHNSON PROFESSIONAL Inc.
Raynham, Massachusetts 02767-0350 (US)


(72) Inventor:
DeCarlo, Alfred F., Jr.
Stamford, CT 06903 (US)

(74) Representative:
Fisher, Adrian John et al
CARPMAELS & RANSFORD
43 Bloomsbury Square
London WC1A 2RA (GB)

(54) Acetabular cup with plug for screw holes

(57) A plug (10) for apertures in an acetabular cup (20) is provided. The plug is particularly useful in plugging screw holes (21). The plug helps to prevent plastic particles from a plastic bearing seated within the cup,

from migrating through the aperture into the bone cavity or acetabulum surrounding the acetabular cup.



EP 1 016 385 A2

Description

FIELD OF THE INVENTION

[0001] The present invention relates to plugs for dome screw holes in the metal cups of a two part acetabular cup system typically comprising a metal cup and plastic socket bearing.

BACKGROUND AND SUMMARY OF THE INVENTION

[0002] A two part acetabular prosthesis typically comprises a metal cup and a plastic socket bearing generally placed within the metal cup. In many of these metal cups, apertures or holes are provided to accept bone screws to screw the cup into the acetabulum to provide additional securement prior to placing the bearing in the cup. One issue with the apertures is that wear of the plastic bearings may generate minute particles that enter the acetabulum through these openings.

[0003] An aperture plug has been described in U.S. Patent No. 5,549,694 where the plug comprises a domed disc that is inserted into a cylindrical aperture and then is deformed to seal the hole.

[0004] Screws are used to augment fixation of an acetabular cup to bone when for example the acetabulum bone is deficient. Generally, a surgeon will select a cup with no holes if no deficiencies are apparent, a cup with two holes, or in situations where bone deficiency is more serious, a cup with more screw holes.

[0005] The screw holes are typically shaped with a spherical opening followed by a narrowed portion and conical portion having an increasing diameter larger than the narrowed portion. Typically, the screw head is spherical and the screw shaft has a diameter smaller than the narrowed portion of the cup opening. This structure permits angular orientation of the screw within the screw hole. Thus, a surgeon is able to select a screw hole and then orient the screw to best locate healthy bone in which to anchor the screw.

[0006] The present invention provides an improved aperture plug adapted for use with certain types of apertures such as screw holes. The present invention provides a plug for use with a screw hole where the screw hole is shaped to receive and allow orientation of an augmentation screw with a spherically shaped screw head.

[0007] In a first embodiment, the plug of the present invention includes a first portion, preferably spherically shaped and sized to fit the spherical opening of the acetabular cup screw hole; a second portion, preferably cylindrical, adjacent the first portion and sized to fit through the narrowed opening of the hole; and a third portion, preferably a deformable disc adjacent the cylindrical portion that can be compressively locked within the hole to seal the hole. The disc portion has an undeformed maximum outside diameter, D_o , that is smaller

than the Diameter D_n of the narrowed opening and a diameter when deformed, D_d , that is greater than the diameter, D_n of the narrowed opening. The disc is inserted from the spherical opening, through the cylindrical opening and is then deformed thereby locking the plug within the hole. In this way, migration of the particles through the aperture is believed to be avoided.

[0008] In another embodiment the plug of the present invention includes a spherically shaped rim portion sized to fit the spherical opening of the screw hole, a cylindrical portion adjacent the rim portion and a deformable expanded portion on the opposite side of the cylindrical portion from the rim portion. In one embodiment, the expanded portion comprises a plurality of axial slits that may be contracted to enable removal of the plug. A variation of this invention provides the deformable axial slits on the spherical rim portion as opposed to the expanded portion.

[0009] One aspect of various embodiments of the present invention may provide an acetabular cup with pre-plugged screw holes having removable plugs placed in the screw holes prior to use. In these various embodiments the plugs may be removed prior to or after implantation.

[0010] The plugs may be placed in the screw apertures of the acetabular cup prior to use and may then be removed as necessary when the physician believes additional securement with screws is desirable in a particular area of the acetabulum. One aspect of a preferred embodiment provides a plug-removing device, e.g., an instrument that engages the plug for removal.

DETAILED DESCRIPTION OF THE DRAWINGS

[0011]

Figure 1 illustrates a sectional view of the plug of the present invention prior to deformation of the plug;

Figure 2 illustrates an acetabular cup having screw holes;

Figure 3 illustrates a cross section of a metal cup with the undeformed plug of Figure 1 inserted therein;

Figure 4 illustrates a cross section of the plug of the present invention in an acetabular cup;

Figure 5 illustrates a tool used to deform the plug with cross-sections of the plug before and after deformation;

Figures 6-9 illustrate second and third embodiments of the present invention;

Figure 10 illustrates a plug removal device.

DETAILED DESCRIPTION OF THE INVENTION

[0012] Figures 1-5 illustrate a first embodiment of the invention.

[0013] Referring now to Figure 1, there is illustrated a plug 10 of the present invention before deformation.

[0014] The plug 10 comprises a spherical rim portion 11 tapering to a cylindrical portion 12, and ending in a domed disc portion 13 adjacent the cylindrical portion 12.

[0015] The plug 10 is preferably made of a deformable, biocompatible material such as a plastic or metal. In a preferred embodiment, a soft, chemically pure titanium is used with a metal cup made of Ti-6Al-4V alloy. The plug 10 may be formed and drawn from a flat piece of metal having the shape of plug 10.

[0016] Referring now to Figures 2-4, there is illustrated a system of the present invention. An acetabular cup 20 for use with the plug 10 of the present invention. The acetabular cup 20 comprises a spherical outer shell 41 with an inner spherical portion 40 having at least one screw aperture 21. In Figures 3 and 4, the plug 10 is inserted into a screw aperture 21 of the acetabular cup 20. The aperture 21 has an internally located (i.e. towards the inner spherical portion 40 of the cup) spherically shaped opening 22, a narrowed cylindrical opening 23 having a diameter D_n , and an externally located (i.e. towards the external surface 25 of the cup 20) conically shaped conical opening 24. The diameter D_n of the cylindrical opening 23 is smaller than the minimum diameter D_x of the spherical opening 22 and the conical opening 24.

[0017] The spherical portion 11 of the plug 10 is shaped to fit within the spherical opening 22. The diameter of the conical portion 12 and the diameter D_o disc portion 13 are each less than the Diameter D_n of the narrowed opening 23 so that the disc 13 extends through the narrowed opening 23 and the spherical portion 11 sits on the surface of the cup 20 that forms the spherical opening 22.

[0018] Referring now to Figure 4, the plug 10 is illustrated in the aperture 21 deformed by the instrument 30 of Figure 5. The instrument 30 includes an end 31 having a diameter D_i smaller than the smallest inner diameter of the plug 10 and a shape generally the same as the spherical opening 22 and the narrowed opening 23 portions of the screw aperture 21. Once the plug 10 is placed in the aperture 21 as illustrated in Figure 1 and the end 31 of the instrument is placed in the plug 10 and is used to deform the disc 13 in a direction towards the exterior of the cup 20. As illustrated in Figure 4 the resulting diameter D_f of the deformed disc 13 is greater than the diameter D_o of the undeformed disc 13. Also, the disc 13 extends into the conical portion 24 of the aperture 21, which has a larger diameter than the narrowed opening 23 diameter D_n . The plug 10 in the deformed position engages three surfaces, the spherical opening surface 22, the narrow opening surface 23

and the conical opening surface 24.

[0019] Referring now to Figures 6-10 there is illustrated another embodiment of the present invention. Plugs 50, 50a comprise respectively a rim portion 51 ending on one end in a top 55, 55a having a coined slit 56, 56a extending only partially through the top 55 55a. The coined slit 56, 56a, will facilitate puncturing for removal with the plug remover 60 (Fig. 1c). The rim portion 51, 51a tapers to a cylindrical portion 52, 52a and end in a skirt portion 53, 53a including tabs 54, 54a extending outwardly.

[0020] In use as illustrated in Figure 7, the plug 50 is placed in the screw aperture 21 of the acetabular cup 20. The cup 20 maybe pre-assembled with plug 50 or a plurality of plugs with a plurality of screw apertures ready, for use in surgery. The rim portion 51 of the plug 50 is shaped to fit with the spherical opening 22 while the cylindrical portion 52 is located within the narrowed opening 23 and the skirt portion 53 is located within the conical opening 24.

[0021] In use as illustrated in Figure 8, the plug 50a is placed in the screw aperture 21 of the acetabular cup 20. The cup 20 may come preassembled with plug 50a inserted in the screw aperture 21 or a plurality of plugs may be placed in a plurality of screw apertures, ready for surgery.

[0022] The skirt 53a of the plug 50a is shaped to fit within the spherical opening 22 while the cylindrical portion 52a is located within the cylindrical opening 23 and the rim portion 51a is located within the conical opening 24.

[0023] The diameter of the skirt 53 or 53a and the rim portion 51 or 51a are initially greater than the diameter D_n of the cylindrical opening 23 while the diameter of the cylindrical portion 52 or 52a are sufficiently small to permit the cylindrical portion to sit within the diameter of the narrowed opening 53.

[0024] Referring to Figure 7, the skirt 53 is deformable so that the diameter of the skirt 53 is less than that of the narrowed opening 23 permitting removal from the screw aperture 21 from the side of the inner spherical portion 40 of the cup 20.

[0025] Referring to Figure 8, the skirt 53a is deformable so that the diameter of the skirt 53 is less than that of the narrowed opening 23, permitting removal from the screw aperture 21 from the side of the external surface 25 of the cup.

[0026] Figure 10 illustrates a plug remover 60, which can be used as part of the system of the present invention. The plug remover 60 comprises a handle 61 and harpoon 62 with an insertion end 63 having a tapered, pointed end 64.

[0027] In use, the insertion end 63 of the plug remover 60 is inserted through the slot 56 or 56a in the end 55 or 55a of the plug 50 or 50a. Figure 9 illustrates the instrument 62 of the plug remover 60 inserted through the slot 56 and rotated about 90°. The plug 60 may now be removed from the cup 20 by pulling on the

handle 61 of the plug remover 60. The pulling force causes the tabs 54 of the skirt 53 to deform inward permitting the skirt 53 to pass through the narrowed opening 23 to remove the plug 50 from the cup 20.

[0028] The plug 50 in Figure 7 may be removed prior to surgical placement of the cup 20 or after placement of the plug 50a may be removed prior to surgical placement because the plug is removed from the exterior side which when placed in a patient is not easily accessible.

[0029] The plug remover 60 may also be used where there are no slots 56 or 56a in the plug 10, 50, or 50a. The point 64 at the end 63 of the harpoon 62 may be used to puncture the plug 10, 50 or 50a. The remover 60 may then be rotated so that the end 63 engages the back or end of the plug 60.

[0030] Various embodiments and modifications may be made to the above-described embodiments without departing from the scope of the invention claimed herein.

[0031] The plugs 50, 50a are preferably made of a deformable biocompatible material such as a plastic or metal. In a preferred embodiment, a soft, chemically pure titanium is used with a metal cup made of Ti-6Al-4V alloy. The plugs 50, 50a may be formed and drawn from a flat piece of metal having the shape of plugs 50, 50a.

[0032] Although this invention is described with respect to a particular embodiment, it is to be understood that modifications can be made without departing from the spirit and scope of the invention as will be evident to those of ordinary skill in the art.

Claims

1. An acetabular cup for receiving a bearing, said cup comprising:

A body having an interior surface for receiving the bearing, an exterior surface for engaging bone, and an aperture which passes through the body from the interior surface to the exterior surface, said aperture having:

- (a.) a first portion, which is accessible from the interior of the body and has a cross-section having a first aperture diameter;
- (b.) a second portion, which is contiguous with the first portion, is located radially outward from the first portion and has a second aperture diameter that is greater than said second aperture diameter; and
- (c.) a third portion which is contiguous with the second portion and has a third cup diameter that is larger than said second diameter;

a deformable plug locked within said aperture

so as to seal the aperture, said plug comprising:

- a first plug portion having a first plug diameter, greater than said second aperture diameter;
- a second plug portion having a second plug diameter at least as small as said second aperture diameter; and
- a third plug portion comprising a deformable portion

- (i) prior to removal from said aperture, said deformable portion having a diameter greater than said second diameter of said aperture, and
- (ii) said deformable portion deformed to a diameter less than said second diameter of said aperture when it is removed from said aperture;

wherein prior to removal from said aperture, said first plug portion is located within said first portion of the aperture, said second plug portion is located in said second portion of the aperture, with said third plug portion located in said third portion of the aperture, said plug being thereby locked within said aperture.

2. The acetabular cup of claim 1 wherein said aperture comprises a screw aperture for receiving a bone screw.
3. The acetabular cup of claim 2 wherein said first portion of said aperture comprises a spherically shaped opening, said second portion comprises a cylindrically shaped opening and said third portion comprises a conically shaped opening.
4. The acetabular cup of claim 1 wherein said first portion of said aperture includes a spherical shape
5. The acetabular cup of claim 1 wherein said deformable portion comprises a skirt having slits therein.
6. An acetabular cup for receiving a bearing, said cup comprising:

A body having an interior surface for receiving the bearing, an exterior surface for engaging bone, and an aperture which passes through the body from the interior surface to the exterior surface, said aperture having:

- (a) a first portion, which is accessible from the interior of the body and has a cross-section having a first aperture diameter;
- (b) a second portion, which is contiguous

with the first portion, is located radially outward from the first portion and has a second aperture diameter that is greater than said second aperture diameter; and

(c) a third portion which is contiguous with the second portion and has a third cup diameter that is larger than said second diameter;

a deformable plug locked within said aperture so as to seal the aperture, said plug comprising:

a first plug portion having a first plug diameter, greater than said second aperture diameter;

a second plug portion having a second plug diameter at least as small as said second aperture diameter; and

a third plug portion comprising a deformable portion

(i) prior to removal from said aperture, said deformable portion having a diameter greater than said second diameter of said aperture, and

(ii) said deformable portion deformed to a diameter less than said second diameter of said aperture when it is removed from said aperture;

wherein prior to removal from said aperture, said third plug portion is located within said first portion of the aperture, said second plug portion is located in said second portion of the aperture, with said first plug portion located in said third portion of the aperture, said plug being thereby locked within said aperture.

7. The acetabular cup of claim 6 wherein said aperture comprises a screw aperture for receiving a bone screw.

8. The acetabular cup of claim 7 wherein said first portion of said aperture comprises a spherically shaped opening, said second portion comprises a cylindrically shaped opening and said third portion comprises a conically shaped opening.

9. The acetabular cup of claim 6 wherein said deformable portion comprises a skirt having slits therein.

10. An acetabular cup for receiving a bearing, said cup comprising:

A body having an interior surface for receiving the bearing, an exterior surface for engaging bone, and an aperture which passes through

the body from the interior surface to the exterior surface, said aperture having:

(a) a first portion, which is accessible from the interior of the body and has a cross-section having a first aperture diameter;

(b) a second portion, which is contiguous with the first portion, is located radially outward from the first portion and has a second aperture diameter that is greater than said second aperture diameter; and

(c) a third portion which is contiguous with the second portion and has a third cup diameter that is larger than said second diameter;

a deformable plug locked within said aperture so as to seal the aperture, said plug comprising:

a first plug portion having a first plug diameter, greater than said second aperture diameter;

a second plug portion having a second plug diameter at least as small as said second aperture diameter; and



a third plug portion comprising a deformable disc



(i) prior to insertion in said disc having a concave side, a convex side, and a diameter which is smaller than the first and third aperture diameters and is larger than the second aperture diameter


(ii) with said plug being inserted into the aperture from the interior of the body, with said convex side oriented toward the interior of the body, and



(iii) being buckled as a result of having been deformed so as to have a convex portion oriented toward the exterior of the body;



wherein said first plug portion is located within said first portion of the aperture, said second plug portion is located in said second portion of the aperture, with said third plug portion located in said third portion of the aperture, said plug being thereby locked within said aperture.













(11) **EP 1 016 385 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
19.12.2001 Bulletin 2001/51

(51) Int Cl.7: **A61F 2/34**, A61F 2/30

(43) Date of publication A2:
05.07.2000 Bulletin 2000/27

(21) Application number: 99310569.1

(22) Date of filing: 24.12.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **DeCarlo, Alfred F., Jr.**
Stamford, CT 06903 (US)

(74) Representative: **Fisher, Adrian John et al**
CARMAELS & RANSFORD 43 Bloomsbury
Square
London WC1A 2RA (GB)


(30) Priority: 30.12.1998 US 223486

(71) Applicant: **JOHNSON & JOHNSON
PROFESSIONAL Inc.**
Raynham, Massachusetts 02767-0350 (US)

(54) **Acetabular cup with plug for screw holes**

(57) A plug (10) for apertures in an acetabular cup (20) is provided. The plug is particularly useful in plugging screw holes (21). The plug helps to prevent plastic

particles from a plastic bearing seated within the cup, from migrating through the aperture into the bone cavity or acetabulum surrounding the acetabular cup.



EP 1 016 385 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 31 0569

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 645 606 A (SCHUCH MARTIN ET AL) 8 July 1997 (1997-07-08) * claims 1,2,5,6; figures * * column 4, line 7 - line 23 *	1-9	A61F2/34 A61F2/30
A	-----	10	
A	US 5 782 929 A (SEDERHOLM GARY W) 21 July 1998 (1998-07-21) * claims 1,4,5; figures *	1-4,6-8, 10	
D,A	US 5 549 694 A (DECARLO JR ALFRED F ET AL) 27 August 1996 (1996-08-27) * figures 3-5 *	10	
A	EP 0 499 475 A (SMITH & NEPHEW RICHARDS INC) 19 August 1992 (1992-08-19) * figures 18,19,21 *	1,6,10	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			A61F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 29 October 2001	Examiner Stach, R
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EP 99 31 0569 (P4A01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 31 0569

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

29-10-2001

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5645606	A	08-07-1997	EP	0666068 A1	09-08-1995
			AT	184179 T	15-09-1999
			DE	59408730 D1	14-10-1999

US 5782929	A	21-07-1998	NONE		

US 5549694	A	27-08-1996	AU	688086 B2	05-03-1998
			AU	3104095 A	22-02-1996
			CA	2195855 A1	08-02-1996
			EP	0767635 A1	16-04-1997
			JP	10504208 T	28-04-1998
			WO	9603096 A1	08-02-1996

EP 0499475	A	19-08-1992	US	5226917 A	13-07-1993
			US	5314487 A	24-05-1994
			US	5310408 A	10-05-1994
			AT	141485 T	15-09-1996
			AU	661293 B2	20-07-1995
			AU	1090992 A	20-08-1992
			CA	2061183 A1	15-08-1992
			DE	69212856 D1	26-09-1996
			DE	69212856 T2	06-03-1997
			DK	499475 T3	10-02-1997
			EP	0499475 A2	19-08-1992
			ES	2095395 T3	16-02-1997
			JP	5068690 A	23-03-1993
			AT	193642 T	15-06-2000
			AU	674027 B2	05-12-1996
			AU	5100693 A	29-03-1994
			CA	2143440 A1	17-03-1994
			DE	69328836 D1	13-07-2000
			DE	69328836 T2	30-11-2000
			DK	682507 T3	16-10-2000
			EP	0682507 A1	22-11-1995
			ES	2149212 T3	01-11-2000
			GR	3034281 T3	29-12-2000
			JP	8502906 T	02-04-1996
			PT	682507 T	30-11-2000
			WO	9405234 A1	17-03-1994

EPO FORM P4/95

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.